

© CITY OF SANTA ROSA

IMPROVEMENT PLANS FOR

WATER PUMP STATION 9 ELECTRICAL UPGRADES


CONTRACT NO. C02438




PROJECT START:	
PROJECT END:	
GEN. CONTRACTO	
SUPERINTENDENT	
FOREMAN:	***************************************
CONSTRUCTION MANAGER:	
INSPECTOR:	
RECORD PLANS BY	
ADDITIONAL INFO:	

PROJECT START:	·	
PROJECT END:		Antide (primary professional descriptions)
GEN. CONTRACTOR:		_
SUPERINTENDENT:		
FOREMAN:		
CONSTRUCTION MANAGER:		
INSPECTOR:		****
RECORD PLANS BY:		oto mienina mineralia del
ADDITIONAL INFO:		









LOCATION MAPS

DRA		G IND	<u>EX</u>
SHEET	NO.	SHEET	support support comm
1		COVER	

SHEET NO.	SHEET TITLE
	GENERAL
1	COVER
2	ABBREVIATIONS, LEGEND & NOTES
3	OVERALL SITE PLAN
	CIVIL & MECHANICAL
4	SUMP PUMP PLAN, SECTIONS & DETAILS
5	CIVIL & MECHANICAL DETAILS
	HVAC
6	MECHANICAL SCHEDULES, DETAILS AND NOTES
7	MECHANICAL PLAN
	ELECTRICAL
8	ELECTRICAL SYMBOLS & ABBREVIATIONS
9	S-9 ONE LINE DIAGRAM
10	METER/MAIN SWITCHBOARD MMS ELEVATION
11	ATS & MTS ELEVATION
12	PORTABLE GENERATOR PEDESTAL & FUEL TANK LEVEL PANEL ELEVATION
13	EXISTING MCC-9 ELEVATION
14	AFE VFD ELEVATION
15	AFE VFD MCC START/STOP ELEMENTARY DIAGRAM
16	TYPICAL ELECTRICAL DETAIL NO.1
17	EXISTING BUILDING ELECTRICAL POWER PLAN
	TEMPORARY FACILITY
18	TEMPORARY PUMPING FACILITY SITE PLAN

BEFORE EXCAVATING CALL U.S.A.
UNDERGROUND SERVICE ALERT USA NORTH AT 811 TWO WORKING DAYS BEFORE ALL PLANNED WORK OPERATIONS

CONTRACT NO. C02438 SHEET 1 OF 18

NUMBER POUNDS

PERCENT

LUM MAX MB MBGR

MAXIMUM

METAL BEAM GUARD RAIL

LEGEND LINES APPROXIMATE EXISTING PARCEL **EXISTING PROPOSED** UTILITY & TOPOGRAPHY DROP INLET DROP INLET WITH SIDE OPENINGS 4 SDMH 24"SD STORM DRAIN, MANHOLE & CATCH BASIN SEWER MAIN, MANHOLE O---- SS----& CLEAN OUT SEWER LATERAL & CLEANOUT IRRIGATION CONTROL VALVE BOX & SERVICE FIRE HYDRANT & SERVICE ASSEMBLY 877 WATER MAIN, GATE VALVE, CROSS & ELBOW WATER MAIN, PERMANENT BLOWOFF TEE, GATE VALVE, CROSS & BEND STD 863 & 889 SINGLE WATER SERVICE (SEE PLANS FOR SIZE) DUAL WATER SERVICE STD 864 (SEE PLANS FOR SIZE) TEMPORARY BLOWOFF, REDUCER & TIE-IN END CAP OR PLUG GAS MAIN. VALVE & SERVICE ELECTRICAL MANHOLE TELEPHONE MANHOLE PACIFIC BELL TELEPHONE TEL (TEL) PULL BOX/VAULT E - E -ELECTRICAL CONDUIT & BOX The second second of the secon STREET LIGHT CONDUIT & BOX STREET LIGHT TRAFFIC SIGNAL [TS] TS TRAFFIC SIGNAL PULL BOX JOINT POLE & GUY ANCHOR ____ OH ____ OVERHEAD UTILITY 500 "STREET NAME" STREET ADDRESS STREET SIGN ____ x ____ x ____ FENCE ® PARKING METER SURVEY CONTROL POINT SURVEY MONUMENT AC DIKE CURB & GUTTER TREE PROTECTION ABANDON EXISTING UTILITY TREE TO BE SAVED/PROTECTED

TREE TO BE REMOVED


 \boxtimes

PLAN BACKGROUND NOTES

- EXISTING PLANIMETRIC FEATURES SHOWN ON THESE PLANS ARE BASED ON AVAILABLE RECORD DRAWINGS, MANUFACTURER CUT SHEETS, AND FIELD MEASUREMENTS. NO TOPOGRAPHIC MAPPING OR FIELD SURVEYING WAS COMPLETED DURING THE PROJECT DESIGN.
- 2. CONTRACTOR AND OTHERS USING THESE PLANS SHALL CONFIRM THE LOCATION OF UNDERGROUND UTILITIES AND STRUCTURES WITH THE CITY PRIOR TO COMMENCING POTHOLING AND CONSTRUCTION ACTIVITIES.
 - 3. RIGHT-OF-WAY, BOUNDARY, AND PARCEL LINES SHOWN ARE APPROXIMATE AND FOR GENERAL REFERENCE ONLY. NO BOUNDARY SURVEYING WAS COMPLETED DURING THE PROJECT DESIGN.
- 4. ELEVATIONS NOTED ARE BASED ON THE CITY OF SANTA ROSA VERTICAL CONTROL DATUM (NGVD 29) UNLESS OTHERWISE NOTED.

GENERAL NOTES

- 1. ALL WORKMANSHIP, MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE CITY OF SANTA ROSA STANDARD PLANS, THE CONSTRUCTION SPECIFICATIONS FOR PUBLIC IMPROVEMENTS, THE SPECIAL PROVISIONS FOR THIS PROJECT AND THE STATE STANDARD SPECIFICATIONS AND STANDARD PLANS. THE CONTRACTOR IS RESPONSIBLE FOR UNDERSTANDING ALL STANDARDS PERTAINING TO THIS PROJECT.
- 2. THE CONTRACTOR SHALL CALL UNDERGROUND SERVICE ALERT USA NORTH AT 811 NO LESS THAN 2 WORKING DAYS PRIOR TO ANY EXCAVATION FOR MARK OUTS OF EXISTING UNDERGROUND FACILITIES IN ACCORDANCE WITH SECTION 5-1.36E OF THE SPECIAL PROVISIONS.
- 3. THE LOCATIONS OF UNDERGROUND UTILITIES AND OTHER OBSTACLES SHOWN ON THE PLANS ARE BASED ON THE BEST AVAILABLE INFORMATION. THE CONTRACTOR SHALL POTHOLE AND DETERMINE THE EXACT LOCATION OF ALL POTENTIAL CONFLICTS IN ACCORDANCE WITH U.S.A. LAWS AND THESE SPECIAL PROVISIONS AND THE STANDARD SPECIFICATIONS. IF ANY UNMARKED UTILITIES ARE ENCOUNTERED, OR IF UNABLE TO LOCATE A MARKED UTILITY AFTER POT HOLING, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE OWNER OF THAT UTILITY AND THE ENGINEER.
- 4. THE CONTRACTOR SHALL PROTECT AND PRESERVE CITY MONUMENTS. THE CONTRACTOR SHALL COORDINATE WITH THE CITY ENGINEER 10 WORKING DAYS IN ADVANCE FOR REFERENCING OF EXISTING MONUMENTS TO BE DISTURBED. THE CONTRACTOR SHALL RECONSTRUCT DISTURBED MONUMENTS IN ACCORDANCE WITH CITY STANDARD 280.
- 5. OVERHEAD UTILITY SERVICE DROPS ARE NOT SHOWN ON THE PLANS. THE CONTRACTOR SHALL INVESTIGATE THE SITE AND BE AWARE OF LIMITED CLEARANCES UNDER OVERHEAD UTILITY LINES AND LOW HANGING TREE BRANCHES. THE CONTRACTOR'S TRUCKS AND EXCAVATION EQUIPMENT SHALL BE SIZED SO THAT OVERHEAD WIRES AND TREE BRANCHES ARE NOT DAMAGED.
- 6. ALL EXCAVATED MATERIAL SHALL BE DISPOSED OF AS GENERATED AND AT NO TIME SHALL THE CONTRACTOR PLACE EXCAVATED MATERIAL AT THE WORK SITE.
- 7. THE CONTRACTOR SHALL ONLY REMOVE EXISTING TREES OR SHRUBS AS NOTED ON THE PLANS OR AS DIRECTED BY THE ENGINEER.
- 8. FOR CLARITY OF EXISTING SUBSURFACE CONDITIONS, NOT ALL CROSSWALKS, STOP BARS, OR EXISTING PAVEMENT MARKINGS ARE SHOWN ON THE PLANS. TRAFFIC STRIPES, RAISED PAVEMENT MARKERS AND PAVEMENT MARKINGS DAMAGED DUE TO THE CONTRACTOR'S OPERATIONS SHALL BE REPLACED PER CITY OF SANTA ROSA TRAFFIC STANDARDS PART III, TRAFFIC MARKINGS. PATCHING OF DAMAGED MARKINGS WILL NOT BE ALLOWED WITHOUT PRIOR APPROVAL FROM THE ENGINEER. ALL DAMAGED RAISED PAVEMENT (NON-REFLECTIVE) MARKERS MUST BE CERAMIC.
- CONTRACTOR SHALL KEEP A SET OF PLANS ONSITE THAT IS CONTINUAL AND LEGIBLY UPDATED AS THIS PROJECT PROGRESSES. THIS SET OF AN EXACT COPY SHALL BE GIVEN TO THE ENGINEER AT THE END OF THE WORK.
- 10. ALL FACILITIES AT PUMP STATION 9 SHALL BE ACCESSIBLE AT ALL TIMES TO CITY PERSONNEL WHEN STATION IS IN OPERATION.




Elje & Race
Consulting Engineers
3vd. Suite 120 Santa Rosa, CA 95403 · 707-576-1322


MP STATION 9
AL UPGRADES
3. LEGEND & NOTES

4

C02438 SHEET 2 OF 18

CONTRACT NO.






1. SLAB EXPANSION JOINTS SHALL BE AT 12'-0" EACH WAY MAX WITH WIDTH AND DEPTH TO MATCH EXISTING.

- 2. SURFACE FINISH SHALL BE LIGHT DELAYED BRUSHING, MATCH EXISTING.
- 2. SURFACE FINISH SHALL BE LIGHT DELATED BRUSHING, MAICH EXISTING
- PLACE 1/2" FIBER EXPANSION BETWEEN SLAB AND EXISTING STRUCTURES TO REMAIN.
- 4. PROVIDE 1/2" CHAMFER AT ALL EXPOSED EDGES.
- 5. PROVIDE 2" CONCRETE COVER OVER REINFORCEMENT.
- 6. EXISTING CONCRETE REINFORCED WITH #4 REBAR AT 12" ON CENTER EACH WAY TOP AND BOTTOM.


DRIVEWAY AND WALKWAY


NOT TO SCALE



TRENCH SECTION

NOT TO SCALE





CMU WALL EXTENSION

SCALE: AS SHOWN



Brelie & Race
CONSULTING ENGINEERS

475 Aviation Blvd. Suite 120 · Santa Rosa, CA 95403 · 707-576-1322
www.brce.com

City of Santa Rosa
WATER PUMP STATION 9
ELECTRICAL UPGRADES
CIVIL & MECHANICAL
DETAILS

CONTRACT NO.

C02438
SHEET 5 OF 18
FILE NO. 2024-0001

	MECHANIC	CAL SYMBOLS
SYMBOL	ABBREVIATION	DESCRIPTION
\boxtimes \longrightarrow	CD	SUPPLY DIFFUSER
$\bigcirc \longleftarrow$	RAG, EAG	RETURN/EXHAUST AIR GRILLE
<u> </u>	VD	VOLUME DAMPER
14412		
14×12		DUCT SIZE, FIRST NUMBER IS IN PLANE OF PAGE
14×12L	L	LINED DUCTWORK
+++		DEMOLITION
		TURNING VANES
	FC	FLEXIBLE CONNECTION
i	FD	FIRE OR FIRE SMOKE DAMPER
		SUPPLY DUCT UP
		RETURN/EXHAUST DUCT UP
T	Т	THERMOSTAT
•	POC	POINT OF CONNECTION
(SD)	SD	DUCT SMOKE DETECTOR
		MOTOR-ACTUATOR
	AFF	ABOVE FINISHED FLOOR
	BDD	BACK DRAFT DAMPER
	CD	CONDENSATE DRAIN
	CTE	CONNECT TO EXISTING
	DG	DOOR GRILLE
	DN	DOWN
	DS	DOOR SENSOR
	DWG	DRAWING
	EA	EXHAUST AIR
	(E)	EXISTING
	FLA	FULL LOAD AMPS
	GA	GAUGE
	GSM	GALVANIZED SHEET METAL
	IJS	IN JOIST SPACE
	MBH	THOUSAND BTU PER HOUR
	MCA	MINIMUM CIRCUIT AMPS
	MOCP	MAXIMUM OVER CURRENT PROTECTION
	NTS	NOT TO SCALE
	OA	OUTSIDE AIR
	os	OCCUPANCY SENSOR
	(RE)	RELOCATE EXISTING
	RL	REFRIGERANT LIQUID
	RS	REFRIGERANT SUCTION
	SAD	SEE ARCHITECTURAL DRAWINGS
	SCD	SEE CIVIL DRAWINGS
	SED	SEE ELECTRICAL DRAWINGS
	SMD	SEE MECHANICAL DRAWINGS SEE MECHANICAL DRAWINGS
	SSTL	STAINLESS STEEL
	TYP U/C	TYPICAL LINDEPCLIT DOOP 5/8"
	UON	UNDERCUT DOOR 5/8"
		UNLESS OTHERWISE NOTED
	VD	VOLUME DAMPER
	VIF	VERIFY IN FIELD
	VTR	VENT THROUGH ROOF

	MECHANICA	AL EQUIPA	MENT SCHE	DULE
		Cooling	Heating	Airflow /

Mark	Make / Model	Description	Accessories/ Options	Cooling Capacity	Heating Capacity	Airflow / Press	Min. OA CFM	Notes	Voltage	Phase	FLA	MCA	МОСР	Weight
TL	GRAINGER 4LZ94 (or APPROVED EQUIVALENT)	Line voltage wall mounted thermostat, 30-110 F setpoint range, inductive rating @ 120 V 16 A						Set operate fan above 90 F						
WHP-1		Nominal 5 ton wall mounted heat pump, ECM indoor blower motor, scroll compressor, ball bearing outdoor motor, 2" MERV 13 air filters, fresh air manual damper.	Low leakage economizer with JADE controller	54.5 MBH, 11.0 EER @ AHRI			440 CFM	Connect to operate from the existing wall thermostat	460 V	3 P		14 A	25 A	471 Lbs






EERING nd Street A 95404-4610 office fex	M29511 Exp. Date 6-30-25
office	OF CALIFORN
LC1 #3004	


				FAN SCH	IEDULE	nde produce de la composition della composition de la composition della composition						
MARK	MAKE / MODEL	DESCRIPTION	ACCESSORIES	AIRFLOW	RPM	SOUND LEVEL	NOTES	VOLTS	PHASE	FLA	MOTOR HP	WEIGHT
EF-1	GREENHECK BSQ-240 (or APPROVED EQUIVALENT)		WD-330 backdraft damper, intake with OSHA guard, NEMA 1 disconnect switch, dial on fan 0-10 VDC speed controller, seismically restrained 1" deflection hanging spring isolators	2,500 CFM @ 0.5"WC, 1.52 BHP	1069 RPM	10.2 Sones	Wire to operate from wall thermostat TL	120 V	1 P	3.8 A, 15 A MOCP	3/4 HP	136 Lbs.

		CAL MATERIALS SCHEDULE ON 23 00 00 FOR COMPLETE SPECIFICATIONS AND REQUIREMENTS
ITEM	MAKE / MODEL	MATERIAL DESCRIPTION
HANGER STRUT	SUPERSTRUT SERIES 1400 "GOLDGALV" or equivalent by B-LINE	14 GAUGE, 0.5 MIL ELECTRO GALVANIZED PLATED COATING
EQUIPMENT NAMEPLATES	SETON custom	Engraved acrylic (plastic), black with white border, 3" wide by 1" high with minimum 1/4" lettering.

MECHANICAL GENERAL NOTES

- 1. ALL EXPOSED CONTROL WIRING SHALL BE INSTALLED IN EMT CONDUIT UNLESS CONCEALED IN WALLS OR ATTIC SPACES.
- 2. LABEL ALL EQUIPMENT WITH ENGRAVED PLASTIC TAGS 3"x1" WITH EQUIPMENT TAG NUMBERS.
- 3. INSTALLATION INSTRUCTIONS FOR ALL EQUIPMENT SHALL BE MADE AVAILABLE TO THE BUILDING INSPECTOR AT THE TIME OF INSPECTION.
- 4. SEISMIC SUPPORT AND BRACING FOR ALL DUCTS AND PIPING SHALL BE INSTALLED IN ACCORDANCE WITH CBC CHAPTER 16. STANDARDS FOR SUPPORT AND ANCHORAGE METHOD AND MATERIALS PUBLISHED BY SMACNA AND APPROVED BY THE STATE AGENCIES MAY BE USED.
- 5. MECHANICAL CONTRACTOR SHALL COMPLETE TITLE 24 CERTIFICATE OF INSTALLATION (NRCI-MCH) AND CERTIFICATE OF ACCEPTANCE (NRCA-MCH) FORMS PRIOR TO COMPLETION OF CONSTRUCTION AND SUBMIT TO THE ENGINEER FOR APPROVAL.
- 6. REFER TO SPECIFICATION SECTION 199 FOR ADDITIONAL REQUIREMENTS.







WALL MOUNTED HEAT PUMP

UPBLAST INLINE EXHAUST FAN


WATER PUMP STATION 9
ELECTRICAL UPGRADES
MECHANICAL SCHEDULES
DETAILS AND NOTES CONTRACT NO. C02438

SHEET 6 OF 18





TEP PROJECT #3804



MECHANICAL PLAN

SCALE: 1" = 5' -0"




City of Santa Rosa	SCALE:	SCALE: AS SHOWN	DATE: AUGUST 2024				
WATER PUMP STATION 9	DWN BY: TS	TS	CHK BY: TS				
ELECTRICAL UPGRADES							
				No. Date	Date	Revision	By
MECHANICAL PLAN				S O N	Date	Revision	

CONTRACT NO. C02438

SHEET 7 OF 18






	MISCELLA	NEOUS	ELECTRICAL & INSTRUMENTATION ABBRE	VIATIO	NS	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
&	AND	HOR	HAND-OFF-REMOTE	PRESS	PRESSURE								
@	AT	HP	HORSEPOWER	PRI	PRIMARY	SWITCH	IES — PROCESS	DEVIC	CES — RELAY	(CO	MPONENTS	WIRING	- CONNECTIONS
A	AMBER, AMPERES	HPS	HIGH PRESSURE SODIUM	PROVIDE	FURNISH, INSTALL & CONNECT	FS							
AC	ALTERNATING CURRENT	HS	HAND SWITCH	PRR	POWER RELAY		FLOW SWITCH — CLOSES UPON INCREASING FLOW	$ \begin{pmatrix} CR \\ 1 \end{pmatrix}$	CONTROL RELAY CR1	-RES VVV-	RESISTOR		PANEL OR EQUIPMENT WIRING
AF	AMP FRAME	HTR	HEATER	PS	PRESSURE SWITCH, POWER SUPPLY		CLOSES OF ON INCREASING FLOW	28, 111	WITH NORMALLY OPEN CONTACT ON LINE 28 & NORMALLY CLOSED		POTENTIOMETER		FIELD WIRING
AFF	ABOVE FINISHED FLOOR ANALOG INPUT	HZ	HERTZ (CYCLES PER SECOND) HAZARDOUS AREA, EXPLOSION PROOF	PT	POTENTIAL TRANSFORMER	FS -oro-	FLOW SWITCH -		CONTACT ON LINE 111	-0-7 0 -0-	TOTENTIONETER		TILLE WINNE
AIC	AMP INTERRUPTING CAPACITY SYMMETRICAL	HZD	INTERLOCK	PTT	PUSH TO TEST PROCESS VARIABLE		OPENS UPON INCREASING FLOW	TR 1	TIME DELAY RELAY TR2 -	———	CAPACITOR, FIXED		CONDUCTORS -
AL	RIGID ALUMINUM CONDUIT	1/0	INPUT/OUTPUT	PVC	POLY VINYL CHLORIDE	LS	LEVEL SWITCH -		ADJUSTABLE TIME DELAY RANGE & SETTING AS SHOWN		3,1,1,0,1,0,1,0,1	` \ \	NOT CONNECTED
ALT	ALTERNATOR	ICR	INSTRUMENTATION CONTROL RELAY	PWR	POWER		CLOSES UPON INCREASING LEVEL				CAPACITOR, ADJUSTABLE	\sim	
AM	AMMETER	INST	INSTANTANEOUS	R	RED	LS		TDOE	TIME DELAY ON ENERGIZATION				CONDUCTORS — CONNECTED
ARMS	ARC FLASH REDUCTION MAINTENANCE SYS	ISC	SHORT CKT INTERRUPTING CURRENT (SYMM)	RCT	REPEAT CYCLE TIMER	— o T o —	LEVEL SWITCH — OPENS UPON INCREASING LEVEL	TDOD	TIME DELAY ON DE-ENERGIZATION		DIODE		CONNECTED
AO	ANALOG OUTPUT	ISR	INTRINSICALLY SAFE RELAY	REF	REFERENCE		OPENS UPON INCREASING LEVEL					\simeq	GROUND
AT	AMP TRIP	J	JUNCTION BOX	RIO	REMOTE I/O	PS	PRESSURE SWITCH -	- $(M1)-$	CONTACTOR OR STARTER M1		DIODE, ZENER	-	
ATS	AUTOMATIC TRANSFER SWITCH	К	KILO, PREFIX	RTD	RESISTANCE TEMPERATURE DETECTOR		CLOSES UPON INCREASING	MI	SOUTH OF STATE OF THE STATE OF				CHASSIS OR FRAME GROUND
AWG	AMERICAN WIRE GUAGE	KAIC	KILO-AMPERE INTERRUPTING CAPACITY	RTM	RUN TIME METER	PS	PRESSURE (INCREASING VACUUM)				VARISTOR TRANSIENT VOLTAGE SUPPRESSOR	<i> </i>	
B	BLUE	L	LINE	RTU	REMOTE TELEMETRY UNIT	— of o—	PRESSURE SWITCH — OPENS UPON INCREASING	SV 	SOLENOID		VOLTAGE SURGE SUPPRESSOR,	\longrightarrow	PLUG AND RECEPTACLE
BC	BARE COPPER BELOW FINISHED CEILING	ILA ILG	LIGHTNING ARRESTOR	RVNR	REDUCED VOLTAGE NON-REVERSING		PRESSURE (INCREASING VACUUM)	· ·			AC		
BOD	BIOCHEMICAL OXYGEN DEMAND	ICD	LIGHTING CONTACTOR LIQUID CRYSTAL DISPLAY	(R)	REWIRE, RELOCATE, REVISE, REUSE, REPLACE SHORTING CONTACTOR	TS	TEMPERATURE SWITCH -	CR1		^^^	RESISTANCE TEMPERATURE	<u> </u>	INCOMING LINE
BLK	BLANK	LED	LIGHT EMITTING DIODE	SCH	SCHEDULE		CLOSES UPON INCREASING		NORMALLY OPEN, RELAY CONTACT —		DETECTOR (RTD)		TEDWINAL DLOOKS
BKR	BREAKER	LEL	LOWER EXPLOSIVE LIMIT	SEC	SECONDARY	TC	TEMPERATURE	(105)	ACTUATED BY RELAY CR1		THERMOCOUPLE (T/C)	\otimes \boxtimes	TERMINAL BLOCKS
С	CONDUIT	LGT	LIGHT	SECS	SECONDS	15 —o <u>z</u> o—	TEMPERATURE SWITCH -	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	COIL LOCATED ON LINE 105				TERMINALS
CAP	CAPACITOR	LO	LOW	SEL	SELECTOR	<u> </u>	OPENS UPON INCREASING TEMPERATURE	CR1 — //-	NORMALLY CLOSED,	DEVICES	- MISCELLANEOUS		
СВ	CIRCUIT BREAKER	LOR	LOCAL-OFF-REMOTE	SFA	SERVICE FACTOR AMPS	ZS —	LIMIT SWITCH -		RELAY CONTACT — ACTUATED BY RELAY CR1				CHIELDED CARLE
CBL	CABLE	LOS	LOCK-OUT STOP SWITCH	SP	SETPOINT		CLOSES AT SET LIMIT	TDO			AUDIBLE ALARM		SHIELDED CABLE
CH	CHANNEL	LP	LIGHTING PANELBOARD	SPD	SURGE PROTECTIVE DEVICE	ZS	LIMIT SWITCH -	TR2	NORMALLY OPEN,				
COAX	COAXIAL CABLE	LPU	LINE PROTECTION UNIT LEVEL SWITCH	SPEC	SPECIFICATION STAINLESS STEEL	<u></u> −0< <u>√</u> 0−	OPENS AT SET LIMIT	^	TIME DELAY RELAY CONTACT — CONTACT CLOSES AFTER		BATTERY	SHIELD — CONDUCTOR	
сомм	COMMUNICATION PORT	LSI	LONG, SHORT, INSTANTANOUS	555	SOLID STATE SOFT STARTER	ZS		TDO	TR2 IS ENERGIZED		HEATER		
СР	CONTROL PANEL	М	MOTOR CONTRACTOR	STT	START		PROXIMITY SWITCH — CLOSES UPON DECREASING	TR2	NORMALLY CLOSED, TIME DELAY RELAY CONTACT —			PLA	N - SYMBOLS
CPT	CONTROL POWER TRANSFORMER	MAX	MAXIMUM	STP	STOP		DISTANCE		CONTACT OPENS AFTER		3 PHASE HEATER		CONDUIT, EXPOSED
CR	CONTROL RELAY	МСС	MOTOR CONTROL CENTER	SV	SOLENOID VALVE	ZS		TDO	TR2 IS ENERGIZED	-2775			CONDUIT, IN SLAB
CT	CONSTANT TOROUS	MCM	THOUSAND CIRCULAR MILS	SW	SWITCH	(000)	PROXIMITY SWITCH -	TR2	NORMALLY OPEN,			again made sales sales victo school tot	OR BELOW GRADE
CIQ	CONSTANT TORQUE COPPER, CONDENSING UNIT	MCP	MOTOR CIRCUIT PROTECTOR	SWBD	SWITCHBOARD		OPENS UPON DECREASING DISTANCE	*	TIME DELAY RELAY CONTACT — CONTACT OPENS AFTER				CONDUIT CTUPPED OUT A CAPPED
DC	DIRECT CURRENT	MHD	MANHOLE METAL HALIDE	SWGR SYMM	SWITCHGEAR SYMMETRICAL	WS			TR2 IS DE-ENERGIZED	G	GENERATOR		CONDUIT STUBBED OUT & CAPPED
DET	DETAIL	MIN	MINIMUM	T	TRIP		TORQUE SWITCH -	TR2	NORMALLY CLOSED,				CONDUIT BENDS TOWARD
DI	DIGITAL INPUT	MINS	MINUTES	ТВ	TERMINAL BLOCK		CLOSES UPON INCREASING TORQUE		TIME DELAY RELAY CONTACT — CONTACT CLOSES AFTER	#	3 PHASE MOTOR		OBSERVER
DIA	DIAGRAM	MISC	MISCELLANEOUS	TC	TIME CLOCK	WS	TORQUE SWITCH -	TDO	TR2 IS DE-ENERGIZED	##	# = MOTOR HP		CONDUIT BENDS AWAY FROM OBSERVER
DISC	DISCONNECT	MNFR	MANUFACTURER	TDOD	TIME DELAY ON DE-ENERGIZATION		OPENS UPON INCREASING TORQUE	TR2	CONTACT OPENS AND CLOSES		and a pure Hotop		CONDUIT ENDS
DIV	DIVISION	MOV	MOTOR OPERATED VALVE	TDOE	TIME DELAY ON ENERGIZATION			*	IN A TIMED REPEAT CYCLE	(#)	SINGLE PHASE MOTOR	1	CONDUIT CHANGE IN ELEVATION
DPDT	DIGITAL OUTPUT DOUBLE POLE DOUBLE THROW	MPS	MOTOR PROTECTION SYSTEM MOISTURE SENSOR/SWITCH	TEL	TELEMETRY					HÎP)			CONDOT! CHANGE IN ELEVATION
DWG	DRAWING	MTR	MOTOR	TELCO TEMP	TELEPHONE COMPANY TEMPERATURE					our o	TRANSFORMER	G	BARE COPPER GROUND WIRE
ELEV	ELEVATION	MTS	MANUAL TRANSFER SWITCH	TM	THERMAL MAGNETIC					~~~~			GROUND CONNECTION BOLTED TYPE
EMT	ELECTRICAL METALLIC TUBING	MV	MEDIUM VOLTAGE	тос	TOTAL ORGANIC CARBON		ø				LINE REACTOR		GROUND CONNECTION BOLTED THE
ETM	ELAPSED TIME METER	N	NEUTRAL	TR	TIME DELAY RELAY								GROUND CONNECTION EXOTHERMIC WELD TYPE
(E)	EXISTING FRAME	NC	NORMALLY CLOSED	TRIAD	TWISTED & SHIELDED 3 CONDUCTOR	SWITCH	ES — OPERATOR	DEVICES	- FRONT PANEL	DEVIC	ES — PROTECTIVE		WELD TIFE
FC	FAIL CLOSED, FAN COIL	NEC	NATIONAL ELECTRICAL CODE NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION	TCDR	TEMPERATURE SWITCH TWISTED & SHIELDED PAIR	SW							PULL BOX
FCS	FIELD CONTROL STATION	NIC	NOT IN CONTRACT	TYP	TYPICAL		TOGGLE OR DISCONNECT SWITCH		INDICATING LIGHT, LETTER "X"	-010-	DISCONNECT, 3 POLE		DISCONNECT SWITCH
FLA	FULL LOAD AMPS	NO	NORMALLY OPEN	UG	UNDERGROUND	PB		(X)	INDICATES COLOR: R=RED G=GREEN, A=AMBER, W=WHITE				FIELD CONTROL STATION
FO	FAIL OPEN	NP	NAMEPLATE	UL	UNDERWRITERS LABORATORIES		PUSHBUTTON — NORMALLY OPEN, MOMENTARY		Y=YELLOW, B=BLUE				WITH JUNCTION BOX
FLEX	FLEXIBLE, METAL LIQUID TIGHT CONDUIT	NTS	NOT TO SCALE	UON	UNLESS OTHERWISE NOTED		ACTION ACTION	PTTX	INDICATING LIGHT, PUSH TO TEST	-010-	CIRCUIT BREAKER, 3 POLE	#A 🔀 🗆	FIELD CONTROL STATION WITH #AMP DISCONNECT SWITCH
FROA	FORWARD-REVERSE-OFF-AUTO	(N)	NEW	UPS	UNINTERRUPTIBLE POWER SUPPLIES	PB	PUSHBUTTON —	←			THERMAL MAGNETIC (TM) OR		SPECIAL RECEPTACLE
FV FVNR	FLOW SWITCH OR FULL SPEED FULL VOLTAGE NON-REVERSING	OL OL	ON CENTER OPERATOR INTERFACE	IV	VOLTAGE	<u> </u>	NORMALLY CLOSED, MOMENTARY	-OAMO-	AMP METER		MOTOR CIRCUIT PROTECT (MCP)		
	FULL VOLTAGE REVERSING	OI OI	OPERATOR INTERFACE OVERLOAD	VAR	VOLT AMPS VOLT AMP REACTIVE	PB	ACTION			<u> </u>		J	JUNCTION BOX
FWD	FORWARD	ORP	OXIDATION REDUCTION POTENTIAL	VFD	VARIABLE FREQUENCY DRIVE		DUCUDUITION MEQUANIQUES	(VMO)	VOLT METER	OL	THERMAL OVERLOAD CONTACT	T	THERMOSTAT
(F)	FUTURE	Р	PHASE, POLE	VLV	VALVE	10.0	PUSHBUTTON, MECHANICALLY INTERLOCKED, DOUBLE CIRCUIT —		FLADOSD TIME METER	— 	THERMAL OVERLOAD CONTACT	, <u>A</u>	LIGHTING, FANS, HEATERS
G	GREEN	РВ	PULL BOX	VM	VOLTMETER		NORMALLY CLOSED AND NORMALLY OPEN, MAINTAINED ACTION	ETM	ELAPSED TIME METER		THERMAL OVERLOAD ELEMENT	# (A)	# — CIRCUIT BREAKER NUMBER A — FIXTURE SCHEDULE REF.
GALV	GALVANIZED	РВІ	PULL BOX INSTRUMENT	VTQ	VARIABLE TORQUE	H O A		IDT.	DIN TIME METER		FLICE WITH DLOWN FLICE		a — CONTROL SWITCH REFERENCE
GEN	GENERATOR	PBP	PULL BOX POWER	W	WHITE, WATTS	* ()	SELECTOR SWITCH, 3 POSITION - CONTACT STATUS SHOWN EXISTS	RTM	RUN TIME METER		FUSE WITH BLOWN FUSE INDICATING LIGHT	# 👄	DUPLEX RECEPTACLE
GFI	GROUND FAULT CIRCUIT INTERRUPTER	PE D=	PHOTOCELL	WHM	WATT-HOUR METER		AT POSITION OF H-HAND,	— XS	MULTI-POSITION SWITCH	(b d)		, ,	# — CIRCUIT BREAKER NUMBER TOGGLE SWITCH
GND	GROUND GALVANIZED RIGID STEEL CONDUIT	PF DED	POWER FAIL POWER (PHASE) FAIL BELAY	WM WP	WATTMETER WATERPROOF, WEATHER PROOF		O-OFF, OR A-AUTO		WHERE LETTER "X" IS FUNCTION: A=AMP, V=VOLT		FUCE	# \$ ²	# — CIRCUIT BREAKER NUMBER
GRS-PVC	PVC COATED GRS CONDUIT	PH	POWER (PHASE) FAIL RELAY HYDROGEN ION CONCENTRATION	WS	TORQUE SWITCH, WATER SURFACE	2-1 1-2	SELECTOR SWITCH, 2 POSITION -		,		FUSE	" · a	SUBSCRIPT — CIRCUIT CONTROLLED SUPERSCRIPT — BLANK = 1 POLE
НС	PUSHBUTTON	PLC		XFMR	TRANSFORMER		CONTACT STATUS SHOWN EXISTS AT POSITION AS SHOWN			< √ 52→>	MEDIUM VOLTAGE		2 = 2 POLE
Н	HIGH	PM	POWER MONITOR	XS	MISCELLANEOUS SWITCH		Somon no onomin				DRAWOUT BREAKER	#	CONDUIT #
HID	HIGH INTENSITY DISCHARGE	PMP	PUMP	Υ	YELLOW					$\langle \longleftrightarrow \rangle$	LOW VOLTAGE DRAWOUT CIRCUIT BREAKER	##	EQUIPMENT NUMBER
НОА	HUMAN MACHINE INTERFACE HAND-OFF-AUTO	PNL	PANEL PAIR, TWISTED & SHIELDED CABLE	Z Zc	IMPEDANCE								
LIIOA	HAND-OFFAUTO	<u> </u> FN	ITTING TWISTED & STILLIDED CADLE	[45	LIMIT SWITCH							(##)	PLC I/O TAG NAME

City of Santa Rosa
WATER PUMP STATION 9
ELECTRICAL UPGRADES
ELECTRICAL SYMBOLS &
ABBREVIATIONS

CONTRACT NO.

SHEET 8 OF 18 FILE NO. 2024-0001

TE	
	o. C.M.
(916)	457-8144
© JUNE 202 ATEEM ENG ALL RIGHTS	INEERING



OROFESS/OW

OAD CALCULATIONS MMS	UTILITY SERVICE			GENERA SERVICE	/	PORTABLE GEN SERVICE				
HP DESCRIPTION	LOAD AMPS	QTY LOAD	LOAD VA	RUN AMPS	QTY RUN	RUN VA	QTY RUN	RUN (QTY RUN	RUN VA
300 Pump 9R1~3	361	3	900,389		2	600,260	2	600,260	-	300,130
75 Pump R9R1~2	96	2	159,626		1	79,813	- in-	79,813		79,813
LP-9	27		22,547		of the second	22,547		22,547		22,547
UBTOTAL	1,275		1,082,562	845		702,619		702,619		402,489
IVERSITY FACTOR			65	%			GEN		GEN	
300 HP							SIZE	,	SIZE	
argest motor @ 25% additional				361	0.25	75,032	1	\	500	KW
							1,250	KVA (625	KVA
OTAL						777,652	1504	AMPS	<u> </u>	AMPS
							AMPS=	845	AMPS=	484
/ 480 V, 3 Phase 4 Wire Service Amps =	1	Amps						1	1	
		Multiplier					KVA=	703	KVA=	402
Service Size =	1	Amps						(
MMS Main Breaker =	2,000	Amps					%GEN	>	%GEN	

(7) REMOVE EXISTING LINE REACTORS AND REPLACE VFD IN PLACE.

8 ALL EXISTING WIRES SHALL BE REUSED AND RECONNECTED. CONTRACTOR SHALL PERFORM EXTREME CAUTION TO PREVENT ANY DAMAGE TO THESE WIRES.

9 CONTRACTOR SHALL FIELD VERIFY TO INSTALL NEW CIRCUIT BREAKER IN EXISTING TRANSITION SECTION AS SHOWN.

% Feeder Load = 58.5%

LOAD= 64.4% (LOAD= 64.4%

& Race	CONSULTING ENGINEERS 475 Aviation Blvd. Suite 120 Santa Rosa, CA 95403 · 707-576-1322	
Brelie	475 Aviation Blvd. • Suite 120 • Sa	www.brce.com

		475 Aviation Blvd. • S www.brce.com	By	
			Revision	

CONTRACT NO. CO2438

SHEET 9 OF 18

FILE NO. 2024-0001

METER/MAIN SWITCHBOARD (MMS) NEMA 3R	ATS NEMA 3R	(E) MOTOR CONTROL CENTER-9 (MCC-9) NEMA 12	UPPER EN UNIT LOCA
480V, 3ø, 4 WIRE 2000A 65 KAIC	RATED 65 KAIC (3) 2000:5	1A 480V, 3Ø, 3 WIRE, 2000A, HORIZONTAL COPPER BUS RATED 65 KAIC	
UTILITY METERING WM 2000AT 2000AF 3P ALSIG 4 ALSIG 65 KAIC (MIN) NEUTRAL NEW NO US POOT 8 UFER GROUND WATER GROUND ROD PIPE UTILITY TRANSFORMER SECONDARY UTILITY METERING WM 2000AT 2000AF 3P ALSIG 4 ALSIG 4 UFER GROUND WATER GROUND ROD PIPE UTILITY TRANSFORMER SECONDARY	POO2B MTS NEMA 3R 2000AT 2000AF 3P KIRK-KEY 1-SIO (5) 800AT 3P KIRK-KEY 1-SIO (5)	COSTED PARCE PAR	LOWER UNIT LO PNL9 SEE SHE

BREAKER TO HAVE ARCFLASH REDUCTION, LONG, SHORT, INSTANTANEOUS & GROUND (ALSIG) ADJUSTABLE TRIP UNITS.

5 BREAKER TO HAVE LONG, SHORT, INSTANTANEOUS & GROUND (LSIG) ADJUSTABLE TRIP UNITS.

6 BREAKER TO HAVE LONG, SHORT & INSTANTANEOUS (LSI) ADJUSTABLE TRIP UNITS.

POWER UTILITY SERVICE

DIVISION OF WORK

Primary Conduits **Primary Conductors** Transformer Pad

Transformer

Bollards

Utility Meter

C/T Enclosure

Contact Name: Power Utility:

Address: City/State/Zip:

Phone: Fax: E-mail:

Notes:

Transformer Connections

Transformer Ground Rod Secondary Conduits

Secondary Conductors

Meter Enclosure/Base

Current Transformers C/T

Power Company Information:

1. All Utility Service installation work shall be done by Contractor per Power Utility

2. Contractor shall coordinate and schedule all Power Utility inspections and tests

in strict compliance with Power Utility requirements.

Engineered drawings (which supersedes what is shown on Contract Drawings).

NOTES: (1) ALL LUGS SHALL BE COPPER. SIZE FOR WIRES LISTED IN "CONDUIT & WIRE SCHEDULE".

2 NEW WORK SHOWN IN CLOUDED AREAS.

3 ATS SHALL BE OPEN TRANSITION TYPE.

Meter Room Lock Box

Electrical

X

X

X


X


PG&E

Contractor | Company

X


X






CONTRACT NO. C02438 SHEET 10 OF 18 FILE NO. 2024-0001

(916) 457-8144 © JUNE 2023 ATEEM ENGINEERING ALL RIGHTS RESERVED




120 VAC LP-9 CKT #6 HEATER--(X) HEATER L6B - LIGHT LIGHT RECEPTACLE

MMS ELEMENTARY DIAGRAM





METER/MAIN SWITCHBOARD (MMS) ELEVATION 1 2 NOT TO SCALE

- NOTES: (1) REAR ACCESS SHALL <u>NOT</u> BE REQUIRED TO SERVICE OR REPLACE ANY SWITCHBOARD COMPONENTS.
 - 2) WEATHER WRAP SHOWN ON DETAIL "A" AT LEFT
 - 3 EACH BREAKER SHALL HAVE A PADLOCKABLE HASP TO LOCK BREAKER IN THE OFF POSITION.
 - 4 DEVICES SHALL BE INSTALLED MAXIMUM 66" ABOVE FINISHED FLOOR.









C02438 SHEET 11 OF 18 FILE NO. 2024-0001

CONTRACT NO.


-ENCLOSURE ENGRAVED NAMEPLATE WITH 1/2" LETTERING (TYP) MANUAL TRANSFER SWITCH -ENCLOSURE ENGRAVED NAMEPLATE WITH 1/2" LETTERING (TYP) MTS **AUTOMATIC** TRANSFER SWITCH ATS CONTROLLER / POWER PORTABLE
O GENERATOR O
DISCONNECT MONITOR MAMEPLATE WITH 1/2" WHITE LETTERS ENGRAVED ON RED PHENOLIC PLATE PUSH TO SHUTDOWN O GENERATOR - EQUIPMENT NAMEPLATE 96" (TYP) WITH 1/4" LETTERING (HC - 901)KIRK-KEY -STANDBY O GENERATOR O DISCONNECT INTERLOCK - TWO POSITION PUSH-PULL LATCHED RED MUSHROOM SWITCH OPERATOR r----PFR SPD (TYP) (TYP)

ATS & MTS ELEVATION 1 2 3 4

- NOTES: 1 REAR ACCESS SHALL <u>NOT</u> BE REQUIRED TO SERVICE OR REPLACE ANY COMPONENTS.
 - 2 NEMA 3R ENCLOSURE WITH TYPICAL DIMENSIONS AS SHOWN, OUTDOOR NOT SHOWN FOR CLARITY. ITEMS DRAWN IN DASHED LINES ARE TO BE LOCATED BEHIND DEADFRONT DOORS.
 - 3 EACH BREAKER SHALL HAVE A PADLOCKABLE HASP TO LOCK BREAKER IN THE OFF POSITION.
 - 4 DEVICES SHALL BE INSTALLED MAXIMUM 66" ABOVE FINISHED FLOOR.









PORTABLE GENERATOR PEDESTAL & FUEL TANK LEVEL PANEL ELEVATION

CONTRACT NO. CO2438

SHEET 12 OF 18 FILE NO. 2024-0001






PORTABLE GENERATOR PEDESTAL ELEVATION 1 NOT TO SCALE

NOTES: 1 ITEMS DRAWN IN DASHED LINES ARE TO BE LOCATED BEHIND DEADFRONT DOORS, OUTER DOORS ARE NOT SHOWN FOR ELEVATION CLARITY.

2 HEIGHT OF CABINET SHALL BE 84" (MINIMUM) ABOVE GRADE. PROVIDE TALLER CABINET OR CONCRETE PAD TO MEET THIS HEIGHT. SEE STRUCTURAL DRAWINGS FOR CONCRETE PAD DETAILS.

FABRICATION METHODS


- 1. NEMA 3R WEATHER-PROOFED FOR OUTSIDE INSTALLATION. 2. ALL OUTER DOORS SEALED WITH PERMANENT TYPE GASKETING.
- 3. EXTERIOR FABRICATED FROM HOT DIPPED GALVANIZED SHEET STEEL.
- 5. ALL SEAMS CONTINUOUS WELDED.
- 7. DOOR HINGES AND PINS SHALL BE 316 STAINLESS STEEL.
- 8. NO SCREWS, RIVETS , OR BOLTS SHALL PROTRUDE EXTERNALLY.
- 4. 12 GAUGE EXTERIOR AND 14 GAUGE INTERIOR.
- 6. OUTER DOORS TO BE PADLOCKABLE WITH HEAVY DUTY 3 POINT LATCHES. 15. ALL WIRING SHALL BE PERMANENTLY LABELED WITH
- 9. INTERNAL SCREWS, RIVETS, BOLTS, AND NUTS PERMANENTLY ATTACHED TO THE INSIDE OF THE FRONT DOOR. SHALL BE STAINLESS STEEL. 10. PEDESTAL SHALL BE U.L. LABELED.
- 11. EXTERIOR PANEL COLOR: DESERT TAN (SUBMIT COLOR SAMPLE TO OWNER FOR APPROVAL).
- 12. INTERIOR DEADFRONT DOOR COLOR: WHITE.
- 13. PHENOLIC SCREW MOUNTED NAMEPLATES SHALL BE PROVIDED
- FOR ALL DEVICES ON DEADFRONT.
- 14. FABRICATION AND WIRING SHALL CONFORM TO U.L. 508 AND NEMA STANDARDS.
- WIRE MARKERS ON BOTH ENDS.
- 16. WIRING DIAGRAMS SHALL BE PLACED IN A DRAWING HOLDER
 - 17. AS BUILT WIRING DIAGRAMS SHALL BE SHIPPED WITH EQUIPMENT.



FUEL TANK LEVEL PANEL ELEMENTARY & ELEVATION 1

NOTES: (1) PROVIDE BACKPAN FOR TERMINAL BLOCKS AND FUSES.

2) TYPICAL FOR TANK 2 (LT955B).




Brelje


CONTRACT NO. C02438

SHEET 13 OF 18 FILE NO. 2024-0001

MCC VFD PILOT DEVICES B



- NOTES: 1 NEW WORK SHOWN IN CLOUDED AREAS.
- REMOVE EXISTING LINE REACTORS AND PROVIDE NEW MCC DOOR WITH OPENINGS TO ACCOMMODATE REPLACED VFD, SEE PHOTO "A" & "B".
- 2) INSTALL NEW BREAKER AND PROVIDE NEW NAMEPLATE WITH 1/4" LETTERING AS SHOWN.





						Ву	
						Revision	
						No. Date	
						No.	
DATE. ALCUST 2024	DATE: AUGUST 2024		CHK BY: SMK				
SCALE: AS SELOWER	SCALE: AS SHOWIN	200	DWN BY: XML				
				L			

4			V	D	L	\bigvee	A		0	
OT	Т	0	SCALE							

SEE SHEET 15 FOR VFD CONTROL 2

90" (TYP) - ENCLOSURE NAMEPLATE WITH 1/2" LETTERS

9R PUMP 1 PNL911

PADLOCKABLE
HASP
(TYP)

— REMOVABLE FILTER (TYP)


NOTES: 1 MINIMUM 24" CLEARANCE FOR VENT ON TOP.

2 DEVICES SHALL BE INSTALLED MAXIMUM 66" ABOVE FINISHED FLOOR.


Z:\ACADDWG\2022\2212B\2212Be005.dwg 6/26/2024 3:44 PM ATEEM

CONTRACT NO. CO2438 SHEET 14 OF 18





Brelje



HIM DISPLAY - HUMAN INTERFACE MODULE REMOTE MOUNT ESC SEL NEMA 12 DIGITAL VFD PROGRAMMER/ CONTROLLER ON UPPER CUBICLE DOOR WITH DISPLAY & KEYPAD DEVICE NAMEPLATE WITH 3/16" LETTERING (TYPICÁL) CONTROL RUN POWER CONTROL POWER BLOWN FUSE INDICATOR CONTROL MANUAL PLC (HC-A)(HS-B)START AFTER DELAY SPEED CONTROL SET MANUAL SPEED POTENTIOMETER TO DESIRED (RED) (GRN) BACKUP CONTRO PUMPING RATE - RED NAMEPLATE WITH 1/4" WHITE ENGRAVED LETTERS VFD PANEL DEVICES

AFE VARIABLE FREQUENCY DRIVE MCC START/STOP ELEMENTARY DIAGRAM

CONTRACT NO.

SHEET 15 OF 18 FILE NO. 2024-0001

HANDHOLE

WITH ID MARKER "GROUND ROD"

-1/2"(1)

GROUND GRID

CONNECTION TO GROUND ROD








WATER PUMP STATION 9
ELECTRICAL UPGRADES
TYPICAL ELECTRICAL
DETAIL NO.1 O (1)

CONTRACT NO. C02438 SHEET 16 OF 18 FILE NO. 2024-0001




CONCRETE WALL ANCHOR BOLTS (TYP) -CONDUIT CLAMPS REQUIRED STAINLESS STEEL BOLTS NUTS AND WASHERS AS REQUIRED (TYP) -Z FITTING (TYP) CONDUIT SUPPORT

CONDUIT PIPE STRAP MOUNTING NOT TO SCALE DETAIL

NOTES: 1) THIS DETAIL TYPICAL FOR BOTH VERTICAL AND HORIZONTAL MOUNTING.


- (2) CHANNEL AND ALL SUPPORT DEVICES TO BE RATED PER AREA CLASSIFICATION. FIELD COAT ALL CUTS, ETC. TO MATCH.
- (3) CHANNELS TO BE SPACED 5' MAXIMUM.




EQUIPMENT CONCRETE PAD NOT TO SCALE DETAIL


NOTES: 1) CONCRETE PAD ABOVE FLOOR TO BE POURED AFTER MAIN PAD HAS BEEN POURED. PAD ABOVE FLOOR TO BE POURED PER SECTION 90 OF THE CITY STANDARD SPECIFICATION AND ACCURATELY LEVELED WITHIN 1/16 INCH. REBAR TO BE #4 @ 12" CROSSWAYS & VERTICAL EVERY 6" (MINIMUM) OR AS CALLED OUT IN STRUCTURAL DRAWINGS.

- (2) IF NO BUILDING WALL EXTEND PAD 4" BEYOND ENCLOSURE ON BACK & SIDES.
- (3) CONCRETE DUCT BANKS SHALL EXTEND & CONNECT INTO EQUIPMENT CONCRETE PAD.





UTILITY CONDUIT INSTALLATION (F DETAIL NOT TO SCALE



EXPOSED CONDUIT TRANSITION (c)

DETAIL

-GRS-PVC

COUPLING

- GROUT CURB AROUND ALL SIDES OF CONDUIT WITH BEVELLED CORNERS

- PVC CONDUIT UNDER MCC GRS ELSEWHERE

- ADAPTOR COUPLING

- PVC CONDUIT PER

CONDUIT SCHEDULE

(TYP)

AT BOTTOM

VAULT

WALL

NOT TO SCALE

#2/0 BARE COPPER (TYP)

 $3/4" \times 10'$

NOT TO SCALE

GROUND ROD HANDHOLE

-VAULT LID

 \longrightarrow MOUNT 8"H \times 8"W \times 4"D

- WATERTIGHT CORD GRIP BOTH ENDS OF CABLES

OLFLEX SKINTOP OR EQUAL.

NEMA 4X STAINLESS STEEL

HOFFMAN CHNFSS OR EQUAL.

MONTED NEAR TOP OF STRUCTURE

- FLOWMETER

FLOWMETER

J-BOX

- MANUFACTURER CABLES (TYP)

BELOW GROUND FLOWMETER H

BELOW LID ADJACENT TO FLOWMETER

(2) SUPPORT CABLE PER DWG E16, DETAIL "D".

NOTES: (1) INSTALL WP RECEPTACLE AT 12"

JUNCTION BOX.

DETAIL


NOTES: (1) FLUSH IN PAVED AREAS.

GROUND ROD

ENCASED CONDUITS NOT TO SCALE DETAIL

NOTES: 1 PLACE CONDUIT RUNS OF 4 CONDUITS OR GREATER IN PLASTIC SPACERS (RATED FOR DIRECT BURIAL) EVERY 5' ALONG LENGTH OF RUN.

- PROVIDE 12" (MIN) SEPARATION BETWEEN
 "A, C, D & M" TYPE GROUP AND
 "E, L & P" TYPE GROUP CONDUITS.
- PER SPECIFICATIONS.



GRS INDOORS AND — GRS-PVC OUTDOORS

FINISH SLAB

OR GRADE

2 1/2" (MIN)

3 1/2" HEIGHT ——

NOT TO SCALE

AROUND CONDUIT

COUPLING

FACTORY ELBOW

UNLESS OTHERWISE NOTED

- - (3) TRENCHING & COMPACTED BACKFILL

